

# VT-PDU 4MS / Metered Switched IP PDU

,Metered, switched per outlet  
Up to 32 CAN extensions and sensors









*Perfect for device switching  
& monitoring in IT racks.*



## Specifications

CPU Speed / RAM / OS	2 cores, 720mHz / 128Mb / Linux v.6.2
Ethernet	10/100Mbps
Outlets	x4 IEC C13 outlets, 110-240V AC, 50/60 Hz.
Metered parametrs	Metered per outlet: Voltage, Frequency, Current, Wattage, Active power, Active energy and other...
Inlet	IEC C14 inlet, 110-240V AC, 50/60Hz, Fuse 10A
Reserve power	12V DC terminal for PCB power reservation
USB Type-C	For USB camera, USB flash, USB hub
CAN port	Connect up to x32 sensors & devices
LAN	Ethernet 10/100 Base-T port
SD memory slot	Up to 512 Gb SDHC
Mounting	Wall, 19", vertical bar (purchased separately)
Warranty	3 years
Support	Online portal

## Supports

-  **Centralized Monitoring & Control**
  - Responsive Web Interface
  - SNMP v1, v2c, v3
-  **Scalability**
  - CAN sensor and extensions
  - Modbus TCP/IP, 4-20mA, 0-10V,
-  **Improved security**
  - OpenVPN, SSL, HTTPS
  - Three-tier data access permissions with login
-  **Protocol support**
  - DHCP, HTTP, HTTPS, DynDNS, SMTP, RADIUS,
  - Syslog, NTP server, HTTP request
- API** **Application Programming Interface**
  - XML, JSON
-  **System Usability**
  - Multi-language mobile interface
  - First-time wizard
  - Sensor & outlet parameters graphing
-  **Virtual sensors / devices / elements**
  - PING, Timers, Triggers, Logic schemes,
  - SNMP GET, IP cameras, Groups, Math
-  **Notifications and alerts**
  - E-mail, SMS, Phone dial, SNMP Traps,
  - Web-to-SMS, SMS link
-  **Logging**
  - SD card, USB flash, E-mail, FTP

Monitoring your infrastructure 24/7